

BLADE SPEED RECOMMENDATIONS

Ø mm	Metres per second (m/s)										
	16	20	25	32	35	40	50	63	80	100	125
100	3,050	3,810	4,770	6,110	6,680	7,630	9,540	12,000	15,200	19,000	23,800
115	2,650	3,320	4,150	5,310	5,810	6,640	8,300	10,400	13,200	16,600	20,700
125	2,440	3,050	3,810	4,880	5,340	6,110	7,630	9,620	12,200	15,200	19,000
150	2,030	2,540	3,180	4,070	4,450	5,090	6,360	8,020	10,100	12,700	15,900
175	1,740	2,180	2,720	3,490	3,810	4,360	5,450	6,870	8,730	10,900	13,600
180	1,690	2,120	2,650	3,390	3,710	4,240	5,300	6,680	8,480	10,600	13,200
200	1,520	1,900	2,380	3,050	3,340	3,810	4,770	6,010	7,630	9,540	11,900
225	1,350	1,690	2,120	2,710	2,970	3,390	4,240	5,340	6,790	8,480	10,600
230	1,320	1,660	2,070	2,650	2,900	3,320	4,150	5,230	6,640	8,300	10,300
250	1,220	1,520	1,900	2,440	2,670	3,050	3,810	4,810	6,110	7,630	9,540
300	1,010	1,270	1,590	2,030	2,220	2,540	3,180	4,010	5,090	6,360	7,950
350	870	1,090	1,360	1,740	1,900	2,180	2,720	3,430	4,360	5,450	6,820
400	760	950	1,190	1,520	1,670	1,900	2,380	3,000	3,810	4,770	5,960
450	670	840	1,060	1,350	1,480	1,690	2,120	2,670	3,390	4,240	5,300
500	610	760	950	1,220	1,330	1,520	1,900	2,400	3,050	3,810	4,770
600	500	630	790	1,010	1,110	1,270	1,590	2,000	2,540	3,180	3,970